

40 PIN CUSTOMER

		12'		
(D)	+24V	RED	16G	01
(E)	+24V	RED	16G 16G	31 32
(F)	E-STOP	WHT/RED	16G	AIR SHUTOFF 4
(K)	J1939(+)	YEL	16G	17
(L)	J1939(-)	GRN	16G	18
(M)	SHIELD	BLK/WHT	16G	16
(R)	KEY/STOP/RUN +24V	PINK	16G	26
(T)	THROTTLE PWM	BLU	16G	10
(A)	DIGITAL GND	BRN/WHT		
(B)		BLU YEL	16G	EXTRA 13'
(G)		GRN/YEL	16G	EXTRA 13'
(J)		BRN	16G	EXTRA 13'
(H)		GRN/WHT	16G	EXTRA 13'
(S)	START	YEL	16G	18' TO START SOL
(U)	GND	BLK	16G	

PLUG ALL UNUSED PORTS

08	(ORG) DIGITAL PWR	A
36	WHT COOL LVL	C
09	(BLK) DIGITAL GND	B

DT06-3S

25' FROM 40 PIN

DWG#:	X275	DWG NAME:	HARNESS, ENG C32	DATE:	01/01/07
File:			C:\X275\X275HNS ENG C32 POWER PRODUCTS		
Dwg Not to Scale			Revisions 0		
W.I.Part#			Num. Date:		
Material:			CONTACT: LARRY RITCHIE		
Tolerance:			432-337-3412		
			FAX: 432-335-5926		
			larry@noflo.com		

Whitlock Instrument
1300 N. Texas
Odessa, Tx 79761
WEB SITE: noflo.com