



①	ORG	LUBE TEMP	32-250°F	9'	4
④	WHT/RED	+5V		9'	1
⑤	BRN	LUBE PSI	500PSI	9'	3
⑥	BLK/WHT	GND		9'	2
⑭	WHT/RED	+5V		8'	A
⑮	WHT/GRN	TRANS PSI	500PSI	8'	B
⑯	BLK/WHT	GND		8'	C
⑳	RED	4/20 MA PRESSURE IN	GRAY CABLE	26'	
㉑	WHT	+24V 4/20 OUT	GRAY CABLE	26'	NO CONNECTOR
㉓	GRY	GREASE PUMP POWER +24V		10'	NO CONNECTOR
㉔	BLK	GND		10'	
㉖	BLU				26'
㉗	BLK				BLUE STROBE LIGHT 26'

DIGIKEY PNST00223

yel	
red	DT06-4S
grn	4PIN DEUTSCH
blu	500PSI/TEMP

3PIN DEUTSCH  
DT06-3S

WIRE DETAIL  
PSI LUBE&TRANS  
PN DIGIKEY  
MSP6501P3-1

A=RED (+5V)  
B=WHITE (SIG)  
C=BLACK (GND)  
DEUTSCH DTO4-3P

HPD26-24-31  
DEUTSCH

DWG#: X275	DWG NAME: HARNESS, PUMP DATA (DRAGON)	DATE: 04/11/06
File: C:\X275\X275HNS PUMP DATA DRAGON.DC		Dwg. By: L R
Dwg Not to Scale	Revisions 0	<b>Whitlock Instrument</b> 1300 N. Texas Odessa, Tx 79761 WEB SITE: noflo.com CONTACT: LARRY RITCHIE 432-337-3412 FAX: 432-335-5926 larry@noflo.com
W.I.Part#	Num. Date:	
Material:		
Tolerance:		