

- (A) SOL A GRY
- (B) SOL B BLU
- (C) SOL C GRY/WHT
- (D) SOL D VIO
- (E) SOL E VIO/WHT
- (F) SOL F GRN
- (G) SOL G GRN/YEL
- (H) SOL H PINK

8' TO EXIT JUNCTION

22-18S


Cable Clamp #714-2564
ALLIED # 605-7091 TYPE 3108B 90°

SPLIT 18"

HDP26-24-23SE-L015

Cable Clamp #714-2564
ALLIED # 605-7203 TYPE 3108B 90°


(W) GND BLK



HOBBS PN76074
PRESSURE SWITCH 60PSI

(L) CONV LOCK WHT/BLK

2 FEET FROM EXIT



(T) TEMP ORG

2 FEET FROM EXIT

(U) TEMP BLK/WHT

TRANS TEMP


(R) WHT/GRN

(S) RPM SENSOR WHT/GRN

TWIST

MAG PICKUP

2 FEET FROM EXIT



NEUTRAL F

- #1 F,H
- #2 C,F
- #3 D,F
- #4 D,G
- #5 E,F
- #6 E,G

DWG#: X275	DWG NAME: HARNESS, TRANS ALLISON 9800	DATE: 07/31/06
File: C:\X275\X275HNS TRANS ALLISON 9800	Dwg. By:	
Dwg Not to Scale	Revisions 0	
W.I.Part#	Num. Date:	
Material:		
Tolerance:		

Whitlock Instrument
1300 N. Texas
Odessa, Tx 79761
WEB SITE: noflo.com
CONTACT: LARRY RITCHIE
432-337-3412
FAX: 432-335-5926
larry@noflo.com